

## **Machine Technical Specifications**

### **Ultra-Trak Universal 5 in 1 Application System**

**Part Number:** FT-5017  
**Product Name:** Ultra-Trak Universal Application System, Includes one Ultra-Trak 5-In-1 Applicator Base Unit and one Micro-Trak Detail Applicator.

**Part Number:** FT-2817 28" Head Assembly, FT-3617 36" Head Assembly and FT-4817 48" Head Assembly

#### **Technical Data on Ultra-Trak Applicator Base Unit**

<b>Chassis/Body Construction</b>	12 ga. high tensile strength, impact resistant high carbon steel.
<b>Tray Housing</b>	18 Gauge high carbon Powder coated steel construction with anti-vibe design.
<b>Motor Pump</b>	Series 4 DC voltage 45 psi pump mechanism with variable volume control circuitry. 31 GPM volume output.
<b>Flow Control</b>	Infinitely adjustable potentiometer to control proprietary flow characteristics to apply broad-spectrum perimeters of water/solvent floor coatings. Preset to 2.2 @ 2000 sf/gal flow rate with FT-2817 head assembly.
<b>Battery</b>	12V 7amp hr sealed gel DC Battery with 8-pin charge/disconnect feature for change out purposes. Run time 2.5hrs. @60 mil output.
<b>Charger</b>	1.5 amp built in Genius Smart Charger with a built in low voltage indicator for 9.6 amps as the default setting.
<b>Head Assembly Feature/Options</b>	28, 36 or 48 inch Head Assembly made for 18 gauge high carbon steel with chemical resistant powder coat with build in catch drip tray.
<b>Spray Manifold</b>	Constructed of aluminum with special series 21D orifices.
<b>Wheel</b>	2 Semi-pneumatic non-marking wheels and 2 ball bearing rear caster wheel designed for full rotation.
<b>Origin</b>	Manufactured and assembled in USA.
<b>Warranty</b>	Steel housing – 15 year warranty Other components – 1 year
<b>Weight</b>	59lbs Base Unit (FT-5017) 18lbs 28" Head Assembly (FT-2817) 20lbs 36" Head Assembly (FT-3617) 24lbs 48" Head Assembly (FT-4817)

## Technical Data on Micro-Trak

### Body Construction

Injection mold 60oz high-density polypropylene reservoir removable tank on a 52" anodized aluminum pole.

### Weight

4.5 Pounds

### Flow Control

The flow control mechanism is comprised of a spring loaded actuating rod, which is used to dispense chemical in an intermittent basis.

### Unit Capacity

50oz capacity tank made from HDPE resin with screw cap design.

### Head Assembly

16" HDPE resin construction with a type 60 hook Velcro attachment design on the backing to attach pad.

### Finish Pad

5x18 Ultra Microfiber application pad is comprised of 80% Polyester and 20% Polyamide in a Terry style format. The pad is hypoallergenic, non-electrostatic, lint free and non-abrasive.

### Warranty

Micro-Trak has a 60 day warranty.

### Manufacturer

Fas-Trak Industries  
PO Box 757  
Monee, IL 60449  
Office: 708-570-0650  
Fax: 708-570-0653

[www.Fas-TrakInd.com](http://www.Fas-TrakInd.com)